









# ECCO 120 BFT

# Portal turnstile, 120° separation, with full-height motorized swing door

Especially well suited for outdoor plant access points.

Passage for persons in wheelchairs, with strollers, bikes or bulky luggage.




Motorized





Up to 20 P/min.




parameters


















- ✓ Combination with swing door
- ✓ Simple installation
- √ Vandal-proof
- ✓ One or two directions operation
- ✓ Direction of entry can be modified
- ✓ Durable quality✓ Integrated LOGITURN control
- ✓ Maintenance-free mechanics
- ✓ Pass counter
- ✓ Accessible electronics









# **Description**

The motorized full-height turnstile ECCO 120 BFT allows the passage of persons in wheelchairs, with strollers, bikes or bulky luggage.

ECCO 120 BFT is particularly suitable for perimeter protection of factories, as well as for stadiums, leisure parks and entries from garages into buildings.

ECCO 120 BFT is suitable for one- or two-way operation and provides a high degree of comfort through the 120° division while offering safe separation of persons.

# **Application Areas**

- Factory security
- Stadiums and leisure facilities
- · Parks und parking garages

#### **Technical Characteristics**

Power Supply: 230V ~ 50-60 Hz

Power Consumption: 40Wh
Connected value: 100VA
Pass frequency up to: 20 P/min.
Storage Temperature: -40°C to +50°C
Operating Temperature: -20°C to +40°C \*1)
Portal Width / Height: 2.623 mm / 2.252 mm

(Height roof included): (2.334 mm) Depth: 1.280 mm

Lane Width / Height: 600 mm / 2.050 mm

Mass: 381 kg

Interfaces: RS485, potential free

contacts, optical coupler inputs, optional RS232

Material: Stainless steel 1.4301,

Aluminum powder

coated

Economic Lifetime: 18 years

\*1) below -20°C to -30°C only with winter package

### Models

**6ELK3A0BB-T** ECCO 120 BFT LT w/ motor door BASIC **6ELK3A0BC-T** ECCO 120 BFT LT w/ motor door CrNi

### **Extras/Options**

6ED-D1K5-B 6ED-R1K5-B	ECCO Roof BASIC, depth 1.500mm ECCO Roof BASIC, depth 2.500mm
6ED-D3U5-C	ECCO Roof COMFORT, depth 1.624mm
6ED-R3U5-C	ECCO Roof COMFORT, depth 2.624mm
62710-N	Drain pipe CrNi-steel
22195-N	Surcharge custom RAL color (CrNi-vers.)
22198-N	Color coating for BASIC-version
21764-N	RED/GREEN signal light 60 mm
22803-N	Fastener set FFO-03
22816-B	Base console set FU-06

### Possible accessories

Reader columns Reader mountings

